

730 coupling

Ref.	D x D
IE7306000V160	16 x 16

suitable for dripline with an internal diameter from 13,80 to 14,10 mm



732 male adaptor

Ref.	D x G
IE73260M0V16B	16 x 1/2"
IE73260M0V16C	16 x 3/4"

suitable for dripline with an internal diameter from 13,80 to 14,10 mm



733 offtake with rubber

Ref.	D	Hole
IE7336000V160	16	12 mm

suitable for dripline with an internal diameter from 13,80 to 14,10 mm.
For assembly make hole with items FUS - FUT - PNZ



734 90° tee

Ref.	D x D x D
IE7346000V160	16 x 16 x 16

suitable for dripline with an internal diameter from 13,80 to 14,10 mm



735 90° elbow

Ref.	D x D
IE7356000V160	16 x 16

suitable for dripline with an internal diameter from 13,80 to 14,10 mm



737 offtake with rubber

Ref.	D	Hole
IE7376000V160	16	17 mm

suitable for dripline with an internal diameter from 13,80 to 14,10 mm



738 offtake with rubber

Ref.	D	Hole
IE7386000V160	16	16 mm

suitable for dripline with an internal diameter from



830 coupling

Ref.	D x D
IE8306000N160	16 x 16
IE8306000M170	17 x 17 *
IE8306000N200	20 x 20



* brown colour

832 male adaptor

Ref.	D x G
IE83260MON16B	16 x 1/2"
IE83260MON16C	16 x 3/4"
IE83260MOM17B	17 x 1/2" *
IE83260MOM17C	17 x 3/4" *

* brown colour



833 offtake with rubber

Ref.	D	Hole
IE8336000N160	16	12 mm
IE8336000M170	17 *	12 mm
NEW IE8336000N200	20	12 mm

for assembly make hole with items FUS - FUT - PNZ . * brown color



834 90° tee

Ref.	D x D x D
IE8342000N050	for minidrip®
IE8346000N160	16 x 16 x 16
IE8346000M170	17 x 17 x 17 *
IE8346000N200	20 x 20 x 20

* brown colour



835 90° elbow

Ref.	D x D
IE8352000N050	for minidrip®
IE8356000N160	16 x 16
IE8356000M170	17 x 17 *
NEW IE8356000N200	20 x 20

* brown colour



836 barbed tee

Ref.	D x D x D
IE8362000N050	for minidrip®



837 offtake with rubber

Ref.	D	Hole
IE8376000N160	16	17 mm
IE8376000N200	20	17 mm
IE8376000M170	17 *	17 mm
OEGOP00000170	spare rubber	-

* brown colour



LOW PRESSURE FITTINGS AND VALVES

FITTINGS FOR CLASSIC DRIPLINE

838

offtake with rubber

Ref.	D	Hole
IE8386000N160	16	16 mm
IE8386000M170	17 *	16 mm
NEW IE8386000N200	20	16 mm
IEGDR8000N000	spare rubber	-

* brown colour



847

3 way female threaded head

Ref.	D x G
IE84763FON16D	16 x 1"
IE84763FON20D	20 x 1"



848

4 way female threaded head

Ref.	D x G
IE84864FON16D	16 x 1"
IE84864FON20D	20 x 1"



849

6 way female threaded head

Ref.	D x G
IE84966FON16D	16 x 1"
IE84966FON20D	20 x 1"



839

90° elbow

Ref.	D x D
IE8392000N160	16 x 16
NEW IE8392000N200	20 x 20



840

coupling

Ref.	D x D
IE8403000N160	16 x 16
IE8403000N200	20 x 20



842

male adaptor

Ref.	D x G
IE84230MON16B	16 x 1/2"



842

male adaptor

Ref.	D x G
IE84230MON16C	16 x 3/4"
IE84230MON20B	20 x 1/2"
IE84230MON20C	20 x 3/4"



843

offtake with rubber

Ref.	D	Hole
IE8435000N160	16	12 mm
IE8433000N200	20	12 mm

for assembly make hole with items FUS - FUT



844

90° tee

Ref.	D x D x D
IE8443000N160	16 x 16 x 16
IE8443000N200	20 x 20 x 20



846

90° male tee

Ref.	D x G x D
IE84630MON16B	16 x 1/2" x 16
IE84630MON16C	16 x 3/4" x 16
IE84630MON20B	20 x 1/2" x 20
IE84630MON20C	20 x 3/4" x 20



841

coupling with ring

Ref.	D x D
IE8412000N160	16 x 16 (PP)
IE8412000N200	20 x 20 (PP)
IE8416000N160	16 x 16 (POM)
IE8416000N200	20 x 20 (POM)



845

offtake with ring

Ref.	D	Hole
IE8456000N160	16 (POM)	12 mm
IE8456000N200	20 (POM)	12 mm

for assembly make hole with items FUS - FUT



829

90° tee with ring

Ref.	D x D x D
IE8296000N160	16 x 16 x 16
IE8296000N200	20 x 20 x 20



Perma-Loc Hose Fittings Selection Chart

Nominal Size	Series Number	Acceptable Inside Diameter		Acceptable Wall Thickness	
		Inches	Millimeters	Inches	Millimeters
16 mm	500	0.510 to 0.580	12.9 to 14.7	0.035 to 0.055	0.89 to 1.40
17 mm	550	0.540 to 0.620	13.7 to 15.7	0.045 to 0.060	1.14 to 1.50
18 mm	600	0.590 to 0.630	15.0 to 16.0	0.025 to 0.050	0.64 to 1.27
20 mm	700	0.685 to 0.740	17.4 to 18.9	0.040 to 0.055	1.00 to 1.40
25 mm	800	0.790 to 0.845	20.0 to 21.5	0.045 to 0.065	1.14 to 1.65

C00

NEW

Perma-Loc coupling

Ref.	D x D
IKC005000N500	Series 500 - 16 x 16
IKC005000N550	Series 550 - 17 x 17
IKC005000N600	Series 600 - 18 x 18
IKC005000N700	Series 700 - 20 x 20
IKC005000N800	Series 800 - 25 x 25



F0M

NEW

Perma-Loc fitting with male thread

Ref.	D x G
IKF0M50M5N50B	Series 500 - 16 x 1/2"
IKF0M50M5N50C	Series 500 - 16 x 3/4"
IKF0M50M5N55B	Series 550 - 17 x 1/2"
IKF0M50M5N55C	Series 550 - 17 x 3/4"
IKF0M50M5N60B	Series 600 - 18 x 1/2"
IKF0M50M5N60C	Series 600 - 18 x 3/4"
IKF0M50M5N70B	Series 700 - 20 x 1/2"
IKF0M50M5N70C	Series 700 - 20 x 3/4"
IKF0M50M5N80C	Series 800 - 25 x 3/4"



NPT thread

T00

NEW

Perma-Loc tee

Ref.	D x D x D
IKT005000N550	Series 550 - 17 x 17 x 17
IKT005000N600	Series 600 - 18 x 18 x 18
IKT005000N700	Series 700 - 20 x 20 x 20
IKT005000N800	Series 800 - 25 x 25 x 25



LOW PRESSURE FITTINGS AND VALVES

FITTINGS FOR CLASSIC DRIPLINE

E00 **NEW**

Perma-Loc elbow

Ref.	D x D
IKE005000N500	Series 500 - 16 x 16
IKE005000N550	Series 550 - 17 x 17
IKE005000N600	Series 600 - 18 x 18
IKE005000N700	Series 700 - 20 x 20
IKE005000N800	Series 800 - 25 x 25



FOY **NEW**

Perma-Loc offtake for layflat

Ref.	D	Hole	Hex
IKFOY5000N500	Series 500 - 16	14 mm	10 mm
IKFOY5000N600	Series 600 - 18	14 mm	10 mm
IKFOY5000N700	Series 700 - 20	20 mm	-



P00 **NEW**

Perma-Loc plug

Ref.	D
IKP005000N500	Series 500 - 16
IKP005000N600	Series 600 - 18



Y0M **NEW**

Perma-Loc male Y fitting

Ref.	D x D x G
IKY0M50M5N50B	Series 500 - 16 x 1/2"
IKY0M50M5N50C	Series 500 - 16 x 3/4"
IKY0M50M5N60B	Series 600 - 18 x 1/2"
IKY0M50M5N60C	Series 600 - 18 x 3/4"

NPT thread

