

### Gpipe® - Irriripe® BD

low density polyethylene pipe for irrigation, produced in compliance with the standard ISO 8779: 2010



ISO 8779:2010

| PN 4      |           |           |       |        |       |
|-----------|-----------|-----------|-------|--------|-------|
| Ref.      | Outside Ø | Thickness | Reel  | Euro/m | Stock |
| FTM01604D | 16,0 mm   | 1,4 mm    | 25 m  | 0,354  | ●     |
| FTM01604E | 16,0 mm   | 1,4 mm    | 50 m  | 0,335  | ●     |
| FTM01604F | 16,0 mm   | 1,4 mm    | 100 m | 0,326  | ●     |
| FTM01604N | 16,0 mm   | 1,4 mm    | 500 m | 0,310  | ●     |
| FTM02004D | 20,0 mm   | 1,5 mm    | 25 m  | 0,479  | ●     |
| FTM02004E | 20,0 mm   | 1,5 mm    | 50 m  | 0,453  | ●     |
| FTM02004F | 20,0 mm   | 1,5 mm    | 100 m | 0,441  | ●     |
| FTM02004L | 20,0 mm   | 1,5 mm    | 300 m | 0,420  | ●     |
| FTM02504D | 25,0 mm   | 1,7 mm    | 25 m  | 0,615  | ●     |
| FTM02504E | 25,0 mm   | 1,7 mm    | 50 m  | 0,583  | ●     |
| FTM02504F | 25,0 mm   | 1,7 mm    | 100 m | 0,567  | ●     |
| FTM02504H | 25,0 mm   | 1,7 mm    | 200 m | 0,540  | ●     |
| FTM03204D | 32,0 mm   | 1,9 mm    | 25 m  | 0,889  | ●     |
| FTM03204E | 32,0 mm   | 1,9 mm    | 50 m  | 0,843  | ●     |
| FTM03204F | 32,0 mm   | 1,9 mm    | 100 m | 0,819  | ●     |
| FTM03204H | 32,0 mm   | 1,9 mm    | 200 m | 0,780  | ●     |
| FTM04004F | 40,0 mm   | 2,4 mm    | 100 m | 1,240  | ●     |
| FTM05004F | 50,0 mm   | 3,0 mm    | 100 m | 1,900  | ●     |
| FTM06304F | 63,0 mm   | 3,8 mm    | 100 m | 3,000  | ●     |

Diameter 16 not included in ISO 8779. Diameters 20 and 25 over-thickness compared to ISO 8779

| PN 6      |           |           |       |        |       |
|-----------|-----------|-----------|-------|--------|-------|
| Ref.      | Outside Ø | Thickness | Reel  | Euro/m | Stock |
| FTM01606D | 16,0 mm   | 1,5 mm    | 25 m  | 0,365  | ●     |
| FTM01606E | 16,0 mm   | 1,5 mm    | 50 m  | 0,346  | ●     |
| FTM01606F | 16,0 mm   | 1,5 mm    | 100 m | 0,336  | ●     |
| FTM01606N | 16,0 mm   | 1,5 mm    | 500 m | 0,320  | ●     |
| FTM02006D | 20,0 mm   | 1,9 mm    | 25 m  | 0,535  | ●     |
| FTM02006E | 20,0 mm   | 1,9 mm    | 50 m  | 0,508  | ●     |
| FTM02006F | 20,0 mm   | 1,9 mm    | 100 m | 0,494  | ●     |
| FTM02006L | 20,0 mm   | 1,9 mm    | 300 m | 0,470  | ●     |
| FTM02506D | 25,0 mm   | 2,3 mm    | 25 m  | 0,798  | ●     |
| FTM02506E | 25,0 mm   | 2,3 mm    | 50 m  | 0,756  | ●     |
| FTM02506F | 25,0 mm   | 2,3 mm    | 100 m | 0,735  | ●     |
| FTM02506H | 25,0 mm   | 2,3 mm    | 200 m | 0,700  | ●     |
| FTM03206D | 32,0 mm   | 2,9 mm    | 25 m  | 1,277  | ●     |
| FTM03206E | 32,0 mm   | 2,9 mm    | 50 m  | 1,209  | ●     |
| FTM03206F | 32,0 mm   | 2,9 mm    | 100 m | 1,176  | ●     |
| FTM03206H | 32,0 mm   | 2,9 mm    | 200 m | 1,120  | ●     |
| FTM04006F | 40,0 mm   | 3,7 mm    | 100 m | 1,780  | ●     |
| FTM05006F | 50,0 mm   | 4,6 mm    | 100 m | 2,750  | ●     |
| FTM06306F | 63,0 mm   | 5,8 mm    | 100 m | 4,350  | ●     |

### Gpipe® - Irriripe® BD grey

low density polyethylene pipe for irrigation, produced in compliance with the standard ISO 8779: 2010



| PN 4       |           |           |       |        |       |
|------------|-----------|-----------|-------|--------|-------|
| Ref.       | Outside Ø | Thickness | Reel  | Euro/m | Stock |
| FTM01604NC | 16,0 mm   | 1,4 mm    | 500 m | 0,327  | ●     |
| FTM02004LC | 20,0 mm   | 1,5 mm    | 300 m | 0,451  | ●     |
| FTM02504HC | 25,0 mm   | 1,7 mm    | 200 m | 0,556  | ●     |
| FTM03204HC | 32,0 mm   | 1,9 mm    | 200 m | 0,837  | ●     |
| FTM04004FC | 40,0 mm   | 2,4 mm    | 100 m | 1,329  | ●     |
| FTM05004FC | 50,0 mm   | 3,0 mm    | 100 m | 2,030  | ●     |
| FTM06304FC | 63,0 mm   | 3,8 mm    | 100 m | 3,208  | ●     |

Diameter 16 non-compliant with ISO 8779. Diameters 20 and 25 over-thickness compared to ISO 8779

| PN 6       |           |           |       |        |       |
|------------|-----------|-----------|-------|--------|-------|
| Ref.       | Outside Ø | Thickness | Reel  | Euro/m | Stock |
| FTM01606NC | 16,0 mm   | 1,5 mm    | 500 m | 0,343  | ●     |
| FTM02006LC | 20,0 mm   | 1,9 mm    | 300 m | 0,474  | ●     |
| FTM02506HC | 25,0 mm   | 2,3 mm    | 200 m | 0,749  | ●     |
| FTM03206HC | 32,0 mm   | 2,9 mm    | 200 m | 1,193  | ●     |
| FTM04006FC | 40,0 mm   | 3,7 mm    | 100 m | 1,906  | ●     |
| FTM05006FC | 50,0 mm   | 4,6 mm    | 100 m | 2,946  | ●     |
| FTM06306FC | 63,0 mm   | 5,8 mm    | 100 m | 4,658  | ●     |